



ELT

Single-Port Very High Output Power



PosiCharge ELT is the workhorse of the lineup, powering the hardest-working fleets in some of the largest companies in the world with up to 600 amps. With two models available, the robust ELT charger is ideal for the heaviest manufacturing and distribution applications.

The ELT has been keeping the fleets of some of the world's leading automakers performing at their best for years. And like all PosiCharge chargers, the ELT works with a broad range of battery voltages and has the same data management and on-board intelligence.

MODEL ELT 600

| | |
|-----------------------------|-----------------------------|
| POWER RATING | 36KW |
| UTILITY REQUIREMENTS* | 480VAC, 3 PHASE |
| FULL LOAD AMP DRAW | 60A |
| MAX. CIRCUIT BREAKER RATING | 80A |
| POWER FACTOR | .88 |
| EFFICIENCY | 90% |
| BATTERY VOLTAGE RANGE | 24V - 48V |
| MAX. OUTPUT CURRENT | 600A |
| WEIGHT | 545 LBS |
| DIMENSIONS | 27.25"H X 22.25"W X 35.75"D |
| COMMUNICATION PORT | RS232 |

* 600VAC AND 240VAC ALSO AVAILABLE

MODEL ELT 680+

| | |
|-----------------------------|-----------------------------|
| POWER RATING | 30KW |
| UTILITY REQUIREMENTS | 480VAC, 3 PHASE |
| FULL LOAD AMP DRAW | 48A |
| MAX. CIRCUIT BREAKER RATING | 60A |
| POWER FACTOR | .88 |
| EFFICIENCY | 90% |
| BATTERY VOLTAGE RANGE | 48V - 80V |
| MAX. OUTPUT CURRENT | 300A |
| WEIGHT | 545 LBS |
| DIMENSIONS | 27.25"H X 22.25"W X 35.75"D |
| COMMUNICATION PORT | RS232 |

©AeroVironment, Inc. 2006